

INSTALLATION AND SAFETY INSTRUCTIONS

FOR YOUR SAFETY

WARNING:BE SURE THE ELECTRICITY TO THE WIRES YOU ARE WORKING ON IS SHUT OFF:ETHER THE FUSE IS REMOVED OR THE CIRCUIT BREAKER IS SHUT OFF

GENERAL

You don't need special tools to install this fixture
Be sure to follow the steps in the order given. Under on circumstances should a fixture be hung on house electrical wires nor should a swag type heating system.Read instructions carefully
If you are unclear as to how to proceed, consult a qualified electrician

NOTE:Proper wiring is essential for the safe operation of this fixture

FIXTURE ASSEMBLY

Carefully unpack the box and removed the fixture and all parts from the carton and check that all parts are included as shown in figure. Be careful to misplace any of the screws or parts, which are needed to install this fixture.

INSTALLATION

STEP 1:Connect the stems (U;S)(depending on desired height).Secure them to the nipple of fixture (N), and thread into 180 degree swivel (K).

STEP 2: Remove Cap finial (F) from Mounting screws (Q), Attach Mounting plate (C) with outlet box screws (D) to outlet box (A).

STEP 3:Pull out the source wires from the outlet box (A)
Make wire connections using Wire nuts (B) as following
-- Connect the ribbed wire (W/O marking) or white wire from light to White wire from power source.
--Connect the smooth wire (W marking) or black wire from light to Black wire from power source.
--Attach the ground wire to Mounting plate (C) secured with Ground screw (R) .
Connect it to the house ground wire with the Wire nut (B)

Carefully tuck the wires back into the outlet box.

STEP 4: Raise the Canopy (E) to the Outlet box (A), then secure it to Mounting plate (C) by mounting screws (Q) with the Cap finial (F).

Make sure they do not exceed the maximum wattage specified on the fixture's wattage rating label.

CLEANING

To clean, Wipe fixture with a soft and dry cloth.
Do not use abrasive materials such as csouring pads or powders, steel wool or abrasive paper.

