

## INSTALLATION AND SAFETY INSTRUCTIONS

### GENERAL

1. To ensure the success of the installation, be sure to read these instructions and review the diagrams thoroughly before beginning.
2. All electrical connections must be in accordance with local codes, ordinances, or the National Electrical Code. If you are unfamiliar with methods of installing electrical wiring, secure the services of a qualified licensed electrician.

3. These fixtures can be mounted to an outlet box (optional). The box (optional) must be directly supported by the building structure.

4. Before starting the installation, disconnect the power by turning off the circuit breaker or by removing the fuse at the fuse box. Turning the power off using the light switch is not sufficient to prevent electrical shock.

NOTE: The important safeguards and instructions appearing in this manual are not meant to cover all possible conditions and situations that may occur. It must be understood that common sense, caution, and care are factors which cannot be built into any product. These factors must be supplied by the person(s) caring for and operating the fixture.

CAUTION: Be certain no bare wire strands are exposed outside of wire connectors.

### ASSEMBLY AND INSTALLATION

1. Fit the tubing(15) on the socket(16) and install the bulb.
2. Assemble the glass shade(17), ring(14), cap(13) and arm(9) according to the illustration. Use nut to lock and tighten the spring bracket(8) and ring(14) to the arm(9). Use knob(11) to lock the nylon washer(12) and cap(13) to the arm(9) too.
3. Disconnect the power at main fuse or circuit breaker box. Connect the positive pole wire from the fixture to the positive pole wire from the outlet box(1) with the wire nut(2), and connect the negative pole wire from the fixture to the negative pole wire from the outlet box(1) with the wire nut.
4. Use ground screw(7) to attach the ground wire from the fixture and the ground wire from the outlet box(1) to the mounting strap(6).
5. Thread the long machine screw(3) into the mounting strap(6). Then attach the mounting strap(6) to the outlet box(1) with the machine screw(4).
6. Use the ball nut(10) to lock the wall plate(5) to the long machine screw(3).
7. Adjust the fixture body, and reconnect the power supply.

