



Because Lighting Speaks Volumes

# V8623-6

Catalog #:

Type:

Project:

Prepared By:

1-Light Integrated LED Indoor or Outdoor White Aluminum Convertible Surface Mount, Flush Mount Ceiling Fixture, Wall Mount, or Wall Sconce with Sealed Frosted Polycarbonate Lens Cover and Round Flanged Trim

## Description

This integrated LED indoor or outdoor white aluminum convertible surface mount, flush mount ceiling fixture, wall mount, or wall sconce features a sealed frosted polycarbonate lens cover and round flanged trim. Easily installs into 4" ceiling or wall junction boxes. Use V0621 parts kit (sold separately) to use this fixture as a retrofit. When used as a retrofit, this fixture is compatible with non-type IC (insulation must be kept 3" away) or type IC (suitable for direct contact with insulation) 6" or 5" recessed downlights. Housing and trim features all-aluminum construction. Feel at ease with cast aluminum's corrosion-resistance, high resilience, lasting quality, and inability to rust like steel. Go green and save big. Energy-efficient LED is environmentally friendly and requires substantially less electricity to maintain, passing down cost-cutting savings to you. Features cold temperature startup in weather as low as 20°C. Operates up to 80°C. Perfect complement to indoor or outdoor spaces. Enjoy rain or shine—conveniently suitable for wet locations. Compact light fits easily in small spaces. Feel confident in your choice of classic elegance. Delight in traditional design that complements homestyle surroundings and décor. Solid white finish. Feel confident in a quality product. Integrated LED comes with a 5-year limited warranty.

## Specifications

Style	Traditional
Type of Lighting	Indoor or Outdoor Ceiling Lighting or Wall Lighting
Product Type	Ceiling Fixture or Wall Mount
Product Subtype	Round, Flanged, Flush Mount, Convertible (Ceiling or Wall Mount), Sconce (When Wall-Mounted)
Height (in.)	2.125
Width (in.)	7.25
Length or Extension/Projection (in.)	7.25
Finish	White
Main Material	All-Aluminum Construction (Housing and Trim)
Other Material	Sealed White Frosted Polycarbonate Lens Cover and White Round Flanged Trim
Light Direction	Down (Ceiling-Mounted) or Outward (Wall-Mounted)
Mounting Deck Height (in.)	7.25
Mounting Deck Width (in.)	7.25
Mounting Deck Shape	Circle
Installation Location	Wet
Light #	1

Watts per Light (W)	13
Total Wattage (W)	13
Light Source Included?	Yes (Integrated LED)
Light Bulb(s) Included?	N/A (Integrated LED Light Source Included)
CRI	80
Color Temperature (K)	4000
Lumens per Light	940
Total Lumens	940
Power Factor (Pf)	>.95
Life Rated (Hours)	50,000
Dimmable?	Yes (10% of Output)
Base	N/A (Integrated LED)
Input Voltage (Volts)	120V at 50/60 Hz
Operating Temperature (C°)	-20 to 80
Compliances	NATIONAL ELECTRICAL CODE 410.16 (C1-5): Code C5 for closet luminaire when installed per code.
Safety Ratings	cULus Listed
Assembly	No Assembly Required
Accessory 1 (Sold Separately)	V0621 Parts Kit (Converts Certain Volume Lighting Surface Mounts to Recessed Housing Retrofits)
Integrated LED Warranty	5-Year Limited Warranty

## At a Glance

- Sturdy, Exquisite Construction
- 5-Year Limited Warranty on Integrated LED (Included with Purchase)
- Sealed White Frosted Polycarbonate Lens Cover and White Round Flanged Trim
- Perfect Complement to Indoor or Outdoor Spaces
- Solid White Finish
- High-Quality, Corrosion-Resistant, and Rust-Resistant All-Aluminum (Housing and Trim)
- Go Green—Environmentally Friendly, Energy-Efficient Integrated LED
- Convertible Fixture Can Install as a Ceiling Fixture Flush Mount or Wall Mount Sconce
- Compact Light Fits Easily in Small Spaces
- 940 Lumens / 4000K Color Temperature / 80 CRI
- Dimmable (10% of Output)
- Enjoy Rain or Shine—Conveniently Suitable for Wet Locations
- Features Ability to Start Up in Cold Weather (Operates From -20°C to 80°C)
- Heat-Resistant Components Withstand Up to 13 Watts
- 1-Light Fixture (Integrated LED Included)
- Use V0621 Parts Kit (Sold Separately) to Use This Fixture as a Retrofit (Compatible with Non-Type IC [Insulation Must Be Kept 3" Away] or Type IC [Suitable for Direct Contact with Insulation] 6" or 5" Recessed Downlights)
- Easily Installs Into 4" Ceiling or Wall Junction Boxes
- Individually Inspected for Quality Assurance
- cULus Listed for Safety

